



## Product Instructions

---

### 6334 Series Multi-Tent Installation Instructions

#### 1.0 General Tent Deployment

1. Remove tent from carry case.
2. Lay tent on the ground, roll up one side wall and secure with side wall straps.
3. With one hand holding a tent side, use the other hand to push up on one roof rod until the hub snaps over center forming the roof panel.
4. Lift the entire tent and locate the four (4) support rods. Insert the support rods into the receptacle end of the “Y” bracket of the attachment hardware being used.
5. Tie guy ropes to any secure object. If working on aerial applications, you may tie off to ladder, or down to ground level.

#### 2.0 Hardware Installation

1. For Strand Clamp attachment, use Model #63350 hardware; clamp hardware securely to the strand at approximately 44” centers. Open tent as explained above. Carefully climb ladder, or use bucket, to reach strand with tent. Insert support rods into “Y” bracket receptacle on clamp. Use guy ropes to secure tent. Additional cords may be attached to strand clamp if needed to prevent sway.
2. For Bucket truck attachment, use Model # 63360 hardware; attach one bracket assembly to each side of the bucket. The clamping system is designed to fit multiple styles of buckets. The clamp should fit securely over the rim of the bucket with the arms extending to the outside. For some styles of bucket, it may be necessary to completely remove the clamp assemblies on each bracket and reverse them. Insert the “Y” brackets into the sleeves on each side. Open tent as explained above. Insert support rods into the “Y” brackets on the outside of the extended arms, and adjust to required height. Use guy ropes to secure tent.
3. For Ladder or Pole attachment, use Model #63380 hardware; ensure that entire assembly is firmly secured. On a ladder, use the supplied hooks around the rungs and turn knobs to tighten. Insert the “Y” brackets into the sleeves on each side. For pole attachment, secure supplied chain to one hook. Pass chain around pole and secure to second hook. Then turn knobs to tighten. Insert the “Y” brackets into the sleeves on each side. Open tent as explained above. Insert support rods into the “Y” brackets on the outside of the extended arms, and adjust to required height. Use guy ropes to secure tent.
4. For manhole Guard attachment, use Model #63390 hardware; insert the flanged end of the guard attachment into the hole on the top of two of the vertical supports, either front or rear. Regardless of which support post is used, make sure that the “Y” receptacle is facing the center of the manhole guard. Open tent as explained above. Insert support rods into the “Y” brackets. Use guy ropes to secure tent.



T.A. Pelsue Company

2500 S. Tejon St.

Englewood, CO 80110

Ph: 1-800-525-8460, (303) 936-7432

Fax: (303)934-5581

Web: [www.pelsue.com](http://www.pelsue.com) E-mail: [sales@pelsue.com](mailto:sales@pelsue.com)